

车床型号: SZGH-36J

SZGH-46J

SZGH-42

SZGH-52

合理推荐料机型号:

CN-65

CN-65L [加工 1.5 米棒材, 需加装延伸架]

1. 加工材料外径范围是: 直径 20mm~ 直径 60.0mm。

2. CN-65 型料机加工: 1.2 米棒材, 直径 20.0mm~60.0mm

3. CN-65L 型料机加工: 1.5 米棒材, 直径 20.0mm~65.0mm

#需要加延伸架

Lathe model: SZGH-36J

SZGH-46J

SZGH-42

SZGH-52

Recommended feeder model:

CN-65

CN-65L [To process 1.5m bars, an extension frame

needs to be installed]

1. The outer diameter range of the processed material is: 20mm diameter ~ 60.0mm diameter.

2. CN-65 feeder processing: 1.2m bars, 20.0mm ~ 60.0mm diameter

3. CN-65L feeder processing: 1.5m bars, 20.0mm ~ 65.0mm diameter

#Extension frame required



车床型号: SZGH-25/36J

合理推料机型号:

CN~326[简易放油模机]

1 加 2 材料外径范围是 5.0~20.0.00mm

2 料机本身重量:260.0KG~300.0K67

3 原材料棒料总长度:2.5 米~3.0 米

4 无润滑油保护表面.

缺点: 1 噪音要比标准油膜机大些

2 料机本身重量轻

Lathe model: SZGH-25/36J

Reasonable pusher model:

CN~326[Simple oil film machine]

1 plus 2 material outer diameter range is  
5.0~20.0.00mm

2 The weight of the pusher itself:  
260.0KG~300.0K67

3 The total length of the raw material bar:  
2.5 meters~3.0 meters

4 No lubricating oil to protect the surface.

Disadvantages: 1 The noise is louder than  
the standard oil film machine

2 The weight of the pusher  
itself is light



①车床型号:SZGH-36J

SZGH-46J

SZGH-42

SZGH-52

合理推荐料机型号:

CNT-330[标准油模机]加工范围:建议加工材料外径范围中 200~280mm

优势:

- 1.全程润滑油包围,防止材料外径碰伤.
- 2.减小加工中所产生的噪音.
- 3.料机本身用料重量 300KG~347KG.
- 4.控制系统采用全新数字化伺服控制,送出尺寸稳定性高.
- 5.故障要率很低
- 6.安装洞试采用公/母航插头,快捷方便
- 7.原材料棒材长度为:2.5 米~3 米

① Lathe model: SZGH-36J

SZGH-46J

SZGH-42

SZGH-52

Recommended machine model:

CNT-330 [standard oil mold machine]

Processing range: It is recommended to process materials with an outer diameter range of 200~280mm

Advantages:

1. Surrounded by lubricating oil throughout the process to prevent the outer diameter of the material from being damaged.
2. Reduce the noise generated during processing.
3. The weight of the machine itself is 300KG~347KG.
4. The control system adopts a new digital servo control, and the delivery size is highly stable.
5. The failure rate is very low
6. The installation hole test uses male/female aviation plugs, which is quick and convenient
7. The length of the raw material bar Length: 2.5m~3m



**特點**

機身瘦小，節省安裝空間。

耐磨消音膠管。

车床型号:SZGH-25

SZGH-36J

SZGH-42J

SZGH-52

通用型油浴机:

①全程油保护外径

②加工材料外径范围:6.0mm~42.0mm

③棒材长度:2.5 米~3.0 米.

④电器控制

料机重:200KG

缺点①需单条材料致置加工

②根据车床型号配置料管条数

③车床型号:

SZGH-25 配 2 条内管和 1 条外管

SZGH-36 配 3 条内管和 1 条外管

SZGH-46 配 4 条内管和 1 条外管

Lathe model: SZGH-25

SZGH-36J

SZGH-42J

SZGH-52

Universal oil bath machine:

- ① Outer diameter of full oil protection
- ② Outer diameter range of processed materials: 6.0mm~42.0mm
- ③ Bar length: 2.5m~3.0m.
- ④ Electrical control

Material machine weight: 200KG

Disadvantages ① Single material required for processing

② Configure the number of material tubes according to the lathe model

③ Lathe model:

SZGH-25 with 2 inner tubes and 1 outer tube

SZGH-36 with 3 inner tubes and 1 outer tube

SZGH-46 with 4 inner tubes and 1 outer tube